



## Technical Specs

Details	Values
Operating Voltage	AC 220 - 240V 50 / 60Hz
PF / THD	> 0.95 / <15%
Driver Efficiency	> 85%
LED Make	EDISON / BRIDGELUX / SEOUL
LED Type	Mid Power LED
LED Life	50,000 Hrs
Lumen Efficacy	> 100 Lm/W
CRI	> 80
CCT	2700 ~ 3500K / 5700 ~ 6500K
Beam Angle	> 120°
Body Material	PBT + PC
Diffuser	Frosted
End Cap	G13 (Retrofit)
Body Colour	White
Working Temperature	-20°C to +50°C
Compliance	BIS / LM80 / RoHS
Protection	Open / Short / 2.5KV / IP20

## Variants

Models	Watt	Sizes
		L x W x H (mm)
<b>Batten</b>		
SLT52F10CB	10W	536 x 22.5 x 36.2
SLT54F18CB	18W	1136 x 22.5 x 36.2
SLT54F20CB	20W	1136 x 22.5 x 36.2
SLT54F22CB	22W	1136 x 22.5 x 36.2
SLT54F24CB	24W	1136 x 22.5 x 36.2
SLT54F40CB	40W	1205 x 29.4 x 38.3
<b>Retrofit</b>		
SLT84F18CR	18W	1200 x 26 x 26
SLT84F20CR	20W	1200 x 26 x 26
SLT84F22CR	22W	1200 x 26 x 26
SLT84F24CR	24W	1200 x 26 x 26

# Batten & Retrofit

Fit for

Home / Living Room / Malls / School / Hotel  
/ Office / Hospital / Showroom / Supermarket

Variants 10W 18W 20W 22W 24W 40W