




Flood Light - ECO

Fit for

Hoardings / Advertising Boards / Billboards / Pandals / Bridges / Stadium / Subways / Parking Lots / Factories / Clubs / Hotels / Landscaping Building / Tunnels / Gardens / Stages / etc.

Variants

30W - 200W



Technical Specs

Details	Values
Voltage	AC 100 - 300V 50 / 60Hz
Operating	AC 220 - 240V 50 / 60Hz
PF / THD	> 0.95 / < 10%
Driver Efficiency	> 87%
LED Make	EVERSTAR / BRIDGELUX / SEOUL
LED Type	Mid Power LED
LED Life	50,000 Hrs
Lumen Efficacy	> 100 Lm/W
CRI	> 70
CCT	2700 ~ 3500K / 4000K / 5700 ~ 6500K
Lens / Beam Angle	Yes / > 120°
Body Material	Aluminum Pressure Die Cast + PC Lens
Body Colour	Gray
Working Temperature	-20°C to +50°C
Compliance	BIS / LM79 / LM80 / IP67 / IK08 / RoHS
Surge	4KV Internal (Built-in) / 10KV or 20KV External (Optional)

Variants

Models	Watt
SLFL30CL	30W
SLFL50CL	50W
SLFL100CL	100W
SLFL200CL	200W