



Street Light

Fit for Streets / Roads / Highways / Bridges / Sports Center / Parking Lots / Landscaping / Building / Factories / Garden / Drying Yards / Plantation Area / Perimeter Lighting / Pathways

Variants 12W - 250W



Technical Specs

Details	Values
Voltage	AC 100 - 300V 50 / 60Hz
Operating	AC 220 - 240V 50 / 60Hz
PF / THD	> 0.95 / < 10%
Driver Efficiency	> 87%
LED Make	NICHIA / OSRAM / SEOUL / CREE / BRIDGELUX
LED Type	High Power LED
LED Life	50,000 Hrs
Lumen Efficacy	> 120 Lm/W
CRI	> 70
CCT	2700 ~ 3500K / 4000K / 5700 ~ 6500K
Lens / Beam Angle	Yes / > 120°
Body Material	Aluminum Pressure Die Cast + Toughened Glass / PC Lens
Body Colour	Gray
Working Temperature	-20°C to +50°C
Compliance	BIS / LM79 / LM80 / IP67 / IK08 / RoHS
Dimming	Optional or as per requirement
Surge	4KV Internal (Built-in) / 10KV or 20KV External (Optional)

Variants

Models	Watt
SLSL12CL	12W
SLSL16CL	16W
SLSL18CL	18W
SLSL24CL	24W
SLSL30CL	30W
SLSL36CL	36W
SLSL40CL	40W
SLSL45CL	45W
SLSL48CL	48W
SLSL60CL	60W
SLSL70CL	70W
SLSL72CL	72W
SLSL90CL	90W
SLSL100CL	100W
SLSL110CL	110W
SLSL120CL	120W
SLSL140CL	140W
SLSL150CL	150W
SLSL180CL	180W
SLSL200CL	200W
SLSL250CL	250W

Any wattage up to 250W as per customer requirement upon order.
 # Product / picture & specification are subject to change without prior notice.
 # Product size is approximate and subject to change due to continuous development.